

## MELTING PLATE CANDLES

### RELATED APPLICATION

- 5 This is a Continuation-In-Part application of Serial Number 09/468,970, filed December 21, 1999.

### FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

- 10 Not Applicable.

### BACKGROUND OF THE INVENTION

#### Technical Field

- 15 The present invention relates to means to provide a novel fuel burning element, such as a candle or lamp, which consumes fuel more efficiently while presenting an aesthetically pleasing appearance. The candles or lamps of the present invention comprise a solid fuel element, a consumable wick, and heat conductive means to transfer heat from the burning fuel, i.e. the flame, to the re-
- 20 maining fuel, thereby assuring its more rapid and complete melting and uniformity of temperature.

#### Background Art

- 25 Ordinary candles comprise a vertical, self-supporting body or column of wax, with a substantially horizontal top and a central longitudinal wick which extends through and above the wax. The exposed portion of the wick above the solid wax is lighted by a flame, and the heat generated by the lighted wick melts a small volume of the wax at the top of the candle, proximate the wick, establishing a puddle or reservoir of molten wax to serve as fuel for the flame on the
- 30 wick. The capillary attraction of the molten wax and the wick, which is generally a structure of closely related fibers, causes the molten wax to travel through the

wick to the flame, by which it is consumed. As the wax is consumed in this manner, the body of wax diminishes and the top surface thereof progressively lowers. The upper portion of the wick, extending above the lowering wax, is generally consumed by the flame.

5 Also well known are such candles or lights as tea lights, in which a body of paraffin is located in a container having a wick centrally disposed. At the lower end of the wick is a wick holder or wick clip, which functions to retain the wick in its perpendicular position, even as the paraffin is melted and liquified by the heat of the flame. In most such candles, the wick is a cotton material saturated with  
10 the paraffin, and burns with the paraffin, thus being consumable. In such candles, or lights or warmers employing the same, the visible flame diminishes as the wick is consumed, the container becomes hazardously over-heated by the flame, and the unit is time-limited by the volume of paraffin and size of the wick initially present. Further, after consumption of all of the wax in the unit, the container and the wick holder remain to be disposed of by the consumer.  
15

Similarly, liquid fuel lamps are known in which a wick is supported with one end suspended in a reservoir of liquid fuel, such as lamp oil. By capillary action, the liquid fuel rises through the wick to the upper end thereof, where it is subjected to consumption by a flame. As fuel is consumed by the flame, additional fuel rises through the wick by capillary action to feed and maintain the  
20 flame. Permanent, or non-consumable, wicks are most frequently employed for this type of lamp.

In U. S. Patent No. 4,557,687, Schirneker teaches a fuel element comprising a shell-like elongated housing in which a supply of fuel may be placed,  
25 with a wick immersed in the fuel supply with its upper portion protruding from the top of the housing. When the fuel is a solid fuel, such as paraffin, the wicks must conduct heat into the housing of the fuel in the area of the immersed wicks so as to provide sufficient amounts of molten paraffin to be drawn up in the wick. Such conductivity may be obtained by means of a piece of metal embedded in the  
30 wick. The purpose of the fuel element is to provide a simulated log for a fireplace which does not require a chimney.

In U. S. Patent No. 3,741,711, Bryant teaches a composite decorative candle formed of clear, undyed and unpigmented candle wax in any appropriate candle shape, provided with a centrally recessed glass cylinder into which a replaceable small candle may be placed. Thus, the decorative outer candle may have a refill unit, such as a votive or tea light, placed therein to provide indefinite reusability. If the outer candle body comprises surface ornamentation, a luminescent glow through the candle body results when the inner candle is burned, and the outer candle is not consumed.

U.S. Patent 3,910,753, of Lee, discloses a wax burner comprising a vessel having a heat conducting metal heat sink surrounding and supporting a wick which projects upwardly, and has a heat conductive metal core means conducting heat into the heat sink, which acts as a wax melting surface. The wax burner may be fueled by paraffin wax or other suitable solid fuel, which may be added to the melting surface as required. The burner may constitute one or more burner units. In Lee, however, the fuel is neither supported nor contained by the heat sink, which is configured much like a spool, with upper and lower flanges, or upper and lower flat, horizontal surfaces. The upper flange or upper surface acts as a heating surface, while the lower flange serves as a base for the heat sink, engaging the bottom surface of the burner vessel. Slots in the vertical surface of the heat sink provide means for the wax, melted by the heat sink, to flow from the exterior surface thereof to the internally located wick. Since the wick structure of the patent includes a metal core and a heat conductive metal sleeve about the wick, the wick structure is an integral portion of the heat sink of the burner assembly, and is non-consumable, and requires priming with wax prior to its first use. In use, solid wax is added to the heating surface, and replenished as necessary, or the entire vessel may be filled with wax. It is to be noted that the vessel itself is not used to conduct heat to the fuel, but only to contain it, and that a separate heat transfer system, i.e. the heat sink structure, which is independent of and distinct from the heat radiated by the flame itself, is utilized to achieve burning of the wax fuel. Even with this added heat transfer mechanism to assist in melting of the fuel, complete utilization of all of the fuel in the vessel is una-

chievable, even when the burner is permitted to burn to self-extinguishing, in view of the relative positioning of the lower flange and the wax conducting means of the heat sink (i.e. slots in the vertical surface thereof, above the lower flange).

In U.S. Patent No. 2,713,256, Oesterle et al teach a votive candle having  
5 a wick extending downward in the bottom of the candle into a tapered central body projection, where said wick engages an adapter inserted into the cup for the votive. The adapter is provided with means to support the wick of the candle until the candle has completely burnt out, thereby leaving no wax or wick residue in the cup, enabling a new candle to be inserted into the cup without removal of  
10 the adapter. The adapter does not function to provide a more even or uniform burning of the candle, but to provide a proper positioning of the votive candle. When placed over the adapter, and the upwardly directed tube thereof, the flame on the wick comes into contact with a wicking material retained in the base of the tube, so as to ignite such wicking and assure that all of the melted wax is burned,  
15 thus leaving a clean cup containing no remains of the previous candle when a new candle is put in place.

European Patent Application EP 1 054 054 A1, published November 22, 2000, teaches a candle having a wick clip assembly for candles to be used on a supporting surface, wherein the wick clip provides enhanced control over heat  
20 transfer from the flame to the supporting surface upon which the candle rests. In this patent, the object of the wick clip assembly is to dissipate heat from the flame away from the support surface, essentially the opposite of the goal of the present invention.

A number of additional patents teach the use of heat conductive elements  
25 to liquify solid fuel for consumption at a wick, or to dispense an element such as a fragrance or insect control material. These include U. S. Patents 5,078,591 of Despres; 4,755,135 of Kwok; and 5,425,633 of Cole; as well as PCT Application WO 89/06141, assigned to Lamplight Farms, Inc.

None of the foregoing references, however, provide a long burning candle  
30 or lamp device capable of rapidly and completely melting a solid fuel and ensuring efficient and complete utilization of all of the fuel provided, while providing in-

creased safety and convenient refilling. Further, the concept of the present invention offers highly decorative as well as functional candles and lamps, which may utilize a variety of gel and solid fuels, with the significant advantages of permitting rapid and convenient replacement of one fuel element by another at the whim of the consumer.

### BRIEF SUMMARY OF THE INVENTION

As utilized herein, the term melting plate candle shall encompass the combination of a solid fuel element, and a container or holder for the fuel. On the other hand, the terms fuel container and fuel holder shall be meant to encompass a melting plate comprising means to contain, support and melt the fuel element, a wick affixed to said melting plate, and heat conductive elements to transfer heat from a flame upon said wick to said melting plate. Thus, it may be seen that the melting plate functions to hold the fuel element, while also serving to retain the wick and to conduct heat to the solid fuel element to thereby melt said fuel to provide a liquid fuel to feed to the flame via the wick. Accordingly, the manufacturer may provide melting plate devices and solid fuel elements independently or separately, and the consumer may join the two to form a melting plate candle or fuel burner, with the option to change fuel elements at will.

The present invention provides a means for the burning of solid fuel elements, wherein said means ensures the maximum utilization of the solid fuel provided. The melting plate devices of the present invention comprise a container for gel or solid fuels, and a wick, and provide an improved transfer of heat from a heat source, a flame burning the fuel at the wick, to the remaining fuel and, more importantly, back to the container for said fuel. Such devices are preferably both functional and designed so as to be decorative or esthetically pleasing.

The melting plate candle of the present invention comprises a fuel element, a container for the fuel, which container comprises a heat conductive heat plate, or melting plate, in direct contact, and in supporting or containing relationship, with the fuel element. The melting plate candle of the present invention

may further comprise heat conductive elements to transfer heat by conductive means to the fuel and to the melting plate, in addition to that heat transfer obtained by radiation from the flame. Such conductive elements result in improved transfer of heat from the burning wick to both the fuel and the melting plate, with  
5 which the fuel is in contact, thereby heating the fuel over a relatively large surface. This, in turn, provides for rapid melting of solid and gel fuels, and rapid heating of the thus melted fuels, to provide a more uniformly heated pool of fuel. Since a goal of the present invention is to more rapidly heat the fuel to temperatures which are not readily achieved by a conventional candle or lamp, so as to  
10 more fully melt the solid fuel and to improve consumption of the fuel, the heating plate element shall hereinafter be referred to as a melting plate.

The melting plate, which acts both as a fuel container and a heat transfer means to heat the fuel, is shaped so as to collect the melted or liquified fuel at its lowest point, at which point a wick is located, so as to ensure that all fuel is fed to  
15 the wick, whereby the maximum consumption of the fuel is achieved. Thus, the melting plate is preferably shaped as a bowl, or in the form of a funnel, with the lowest portion thereof preferably, but not necessarily centered. The wick is located so as to be at the lowest portion of the melting plate, and may be positioned in a complementary depression in the fuel container or melting plate. The  
20 entire interior surface of the fuel container is preferably highly heat conductive, and supports, contains, and heats the fuel, although containers in which only a small portion of the interior surface acts as a melting plate are within the scope of the present invention. The heat conductive surfaces of such containers shall be referred to as the melting plate, and candles employing such melting plates shall  
25 be referred to, collectively, as melting plate candles. In the preferred embodiments, the melting plate shall comprise the entire fuel container.

Moreover, the melting plate helps to control the shape and depth of the pool of fuel which is burned at the wick, and to maintain the constancy thereof. It is to be understood that the fuel utilized in the present invention may be initially in  
30 solid or gel form, but must be in liquid form for moving up the wick by capillary action to the flame, where it is consumed. Thus, the fuel used with the melting

plate candle shall be such that it will not be transported by capillary action at ambient or room temperature, but requires heating to a liquified state, i.e. melting, to be subject to wicking action. For convenience, the term solid fuel shall be used hereinafter to refer to fuel in either a gel or conventional solid state, such as conventional candle wax. It is also to be understood that the fuel consumed in the flame at the burning wick is drawn by the wick from a liquid pool of fuel, which pool is formed by melting of the solid fuel, said liquid pool being heated by conductive heat transfer by the melting plate, the wick, and heat exchange elements, in addition to the radiant heat from the flame on the wick. By the use of the melting plate technology of the present invention, in addition to the conventional radiant heating of the surface of the fuel, the size and temperature of the liquid pool of fuel are better regulated, and as a result of greater heat transfer to the fuel, a melted, liquid pool thereof is more rapidly formed and heated to a relatively high temperature, and efficiency of consumption thereof is improved. Because the speed of achieving a liquid pool of fuel is increased, a more efficient consumption of the fuel results, as well as a more complete usage of available fuel, due to the decrease of fuel left unburned on the surface of the melting plate. In preferred embodiments of the present invention, a pool of liquid, i.e. melted, fuel rests upon the surface of the heat conductive melting plate. This pool of fuel may contain unmelted fuel in the solid state, as well as melted fuel.

Generally, the melting plate device embodies both a melting plate and a heat conductive element, which element is in close proximity to the flame, to ensure more uniform and rapid heat distribution from the flame upon the wick. The wick is affixed in its preferred position by means of crimping to a wick clip, press fit, or by other appropriate conventional means, such as by welding, soldering, or cementing, as with an adhesive. The wick may be any filamentary body which is sufficiently sturdy, which will burn with a steady flame, and which is capable of drawing up the molten candle fuel by capillary action. Such a wick may be of any conventional consumable wick material, such as cotton, cellulose, nylon, or paper. The wick may preferably be located in the center of the candle, or may be

off-center as desired. The presence of two or more wicks is also within the scope of the present invention.

The heat conductive element may constitute a portion of the melting plate itself, formed or bent to be in proximity to the flame, or may be a separate assembly which is utilized in conjunction with the melting plate and consumable wick. For example, the melting plate may constitute a bowl shaped container having its outer periphery in close proximity to the flame, such as a container in which the upper lip of the bowl is formed so as to curve back toward the center of the bowl. Alternatively, the melting plate may have one or more raised portions, or lobes, which may act not only to absorb and distribute heat by conduction, but to channel or direct the flow of liquid fuel to the wick, and/or to engage the fuel element in such a manner as to properly position it. Further, the lobes may constitute areas of higher heat conductivity than surrounding areas of the container.

However, as indicated, the heat conductive element may also be a separate and independent assembly, including means to support and locate the wick, which assembly may be replaced as necessary or desired, but is preferably a permanent feature of the melting plate. The heat conductive element assembly may take the form of heat fins or heat conductive surfaces having either vertical or horizontal orientation, or elements of both. In preferred embodiments, such heat conductive elements are heated by contact with the flame, or by radiation of heat from the flame, and conduct such heat to the melting plate and to the fuel so as to more efficiently heat the fuel.

It is to be understood that the heat conductive elements may be so situated and shaped as to engage or interlock with a replaceable or refillable solid fuel element, such as being of a specific shape or configuration that will engage or mate with a complementarily shaped fuel element. In a similar fashion, the heat conductive elements and/or the fuel container may be formed in such a manner as to permit placement of fuel elements of specific configuration, such as balls, cylinders, or cubes, for example, in a preferred position in proximity to the heat conductive elements themselves, or to the wick, in such a manner as to maximize heat transfer to said fuel elements.



The present invention is thus a melting plate candle, said melting plate candle comprising, in its most basic form, a container, and a solid fuel element having a consumable wick, wherein said container is configured so as to cause the flow of liquid fuel to the wick, at which wick the fuel may be burned to produce heat so as to liquify said solid fuel element. In a preferred embodiment, the melting plate constitutes a container comprising a melting plate configured so as to cause the flow of liquid fuel to the wick, a consumable wick, and a heat conductive element to conduct heat from a flame at the wick to the melting plate, which is in contact with a solid fuel element. In such a preferred embodiment, the fuel is a solid wax, which is melted by heat conducted via the heat conductive element and the melting plate, to provide liquid fuel to the flame via the wick.

In one aspect, the invention provides a method for fueling a long-burning melting plate device, wherein replenishment fuel is added as necessary or desired, without the need to extinguish the flame while additional fuel is provided. By use of a conductive melting plate, the solid fuel is heated over a relatively large surface area, to speed the melting and heating of a large volume of solid wax or fuel. The liquid pool of wax or fuel thus formed acts both as a reservoir and a safety feature, since such a pool will act to extinguish a flame at the wick if the pool level becomes excessive, or if the device is tilted excessively, particularly as the melting plate is so configured as to cause liquid fuel to flow to the wick.

The objects of the present invention therefore include providing melting plate candles and lamps, which are:

- (a) capable of burning for extended periods without close attention;
- (b) capable of burning a variety of fuels which may be conveniently and rapidly changed or added as desired;
- (c) able to rapidly produce a pool of melted wax for consumption at the wick;
- (d) highly decorative;
- (h) self cleansing, in the sense that they leave little or no residue of unburned fuels; and
- (i) relatively inexpensive to produce, and economical for the consumer.

The use of the melting plate technology of the present invention may also provide such advantages as elimination of tunneling, significant reduction of retention of wax at the conclusion of the burn, elimination of walking or off-center wicks, while also giving a large pool of liquid wax with a relatively small flame in a relatively short time period. In addition, the container may be of almost any shape desired, providing for great aesthetic possibilities. Since the fuel element is provided as a separate unit, the consumer may be provided a great number of choices as to the color and nature of the fuel, and the configuration of the fuel element may be varied to provide a large choice of shapes, such as seasonably decorative items. For example, shapes such as pumpkins may be provided for Halloween, and wreaths for Christmas. In addition, the fuel element may be so configured as to cooperatively engage the melting plate and/or the heat conductive element, in such a manner as to provide the consumer the greatest degree of ease in placement of the fuel element in optimal position in the melting plate candle, with the least possibility of incorrect placement.

Thus, an object of the present invention is to provide a lamp or candle device, said device comprising, in combination, a fuel element comprising a solid fuel, a container for said fuel element, and, a wick at which said fuel may be burned to produce heat so as to melt said solid fuel, wherein said container is configured so as to cause the flow of melted fuel to said wick.

Accordingly, it is an object of the present invention to provide a melting plate candle, wherein said candle comprises a container for a fuel element comprising a fuel selected from the group consisting of paraffin, beeswax, montan wax, carnauba wax, microcrystalline wax, stearic acid, fatty alcohols, fatty acids, fatty esters, and gels incorporating such fuels, in a form selected from the group consisting of pucks, donuts, chips, slivers, balls, pellets, shavings, particulates, cubes, discs, three dimensional shapes, and wafers, or in any other suitable shape, wherein said container is a concave melting plate further comprising a consumable wick and a heat conductive element chosen from the group consist-

ing of lobes, fins, wick holders, and combinations thereof, and said heat conductive element cooperatively engages said fuel element.

Similarly, a further object of the present invention is to provide a melting plate candle or lamp, said candle comprising, in combination, a meltable solid fuel, a consumable wick, a conductive base upon which said fuel rests, and heat conductive elements by which heat is conducted to said base from a flame upon said wick, whereby a pool of heated liquid fuel is created, wherein said heat conductive base is configured so as to cause the flow of said heated liquid fuel to said wick for combustion, and said base and said elements are configured so as to cooperatively engage said fuel.

Accordingly, an object of the present invention includes providing a melting plate candle comprising a solid or gel fuel, which fuel is melted by a heat conductive element selected from lobes, fins, wick holders, or combinations thereof, said heat conductive element being heated by a flame at a wick, a heat conductive base upon which the fuel rests, the base being configured so as to cause the flow of melted fuel to the wick, and the heat conductive element configured to cooperatively engage the fuel element.

A further object is to provide a melting plate lamp or candle comprising a replaceable fuel element, and a fuel containing device comprising a heat conductive melting plate, a wick, and a heat conductive element to collect heat from a flame at said wick and conduct said heat to said melting plate to thereby melt said fuel and form a pool of liquid fuel on the surface of said melting plate, wherein said containing device is configured to position and engage said fuel on said melting plate for rapid melting, and said melting plate is shaped so as to cause said pool of liquid fuel to flow to said wick.

Also desired is a solid replacement element for a lamp or candle, said element comprising a solid fuel having a consumable wick element. Applicants further teach a device comprising a heat conductive container having affixed thereto a wick, said container configured so as to cause the flow of liquid contents to the wick and to engage and melt a solid fuel element.

These and still other objects and advantages of the present invention will be apparent from the description which follows. The following description is merely of the preferred embodiments, and the claims should be looked to in order to understand the full scope of the invention.

5

## BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates the basic concept of the melting plate candle, in simplified perspective view.

10

Figure 2 illustrates a basic melting plate candle of the present invention, in simplified cross section.

Figures 3a through 3e are perspective views of various exemplary heat conductive elements in the form of wick holders, and fins, which are suitable for use in this invention.

15

Figures 4, and 5 are cross sectional representations of melting plate candles employing melting plates of differing configuration.

Figures 6 and 7 are a top view and a perspective view of an oval melting plate candle employing heat lobes in the form of raised portions of the melting plate.

20

Figure 8 illustrates a perspective view of a melting plate candle employing a wick, and a refill fuel element in the form of a wax ball positioned adjacent the wick by heat lobes formed as part of the melting plate.

25

Figure 9 is a simplified cross sectional view of a floating melting plate candle, comprising a melting plate, heat conductive element in the form of a wick holder having fins, and a solid wax refill segment.

## DETAILED DESCRIPTION OF THE INVENTION

30

Figures 1 and 2 illustrate the concept of the melting plate candle in its most basic form. As illustrated, a heat conductive bowl shaped melting plate, 2, is provided, which transfers heat from the heat source, a flame (not shown) lo-

cated on wick 3, by means of heat conduction, to a solid fuel element, 4, which rests upon the surface of the melting plate. For purposes of illustration, and for clarity, but intending no limitation, the wick is illustrated as being of a relatively large diameter, rather than as a conventional fibrous consumable wick of small diameter. It is to be understood that the wick is conventionally positioned and attached to and within the solid fuel element, 4, such as with a wick clip (not shown). The melting plate, 2, is heated directly by the flame on the wick, 3, either by direct contact therewith, or by radiation, as in Figure 1 and 2, as a result of the melting plate being shaped so as to have a portion in proximity to the flame, the diameter of the melting plate bowl being such as to permit the inner surfaces thereof to absorb appreciable amounts of heat from the flame.

In a melting plate candle apparatus, the wick may be held by a conventional wick clip, or may be held in place by a heat conductive element, such as a wick holder, as shown in Figure 4, or affixed to or retained by the fuel element by other appropriate means. To assure efficient heat exchange between the flame at the wick and the melting plate, the melting plate of Figures 1 and 2 is shaped so as to have a portion, in this case a raised shoulder, 22, of the melting plate, which is in proximity to, and heated by, the flame of the burning wick, which results in heat being transferred rapidly to the fuel by both conduction through the melting plate and by radiation from the flame. The solid fuel element is subject to melting from heat from the flame and the melting plate. As opposed to a conventional candle, transfer of heat from the flame to the fuel with a melting plate device is primarily by conduction, either through the melting plate or through additional heat conductive means, rather than by radiation, and is thus considerably more efficient, resulting in more rapid and more uniform melting of solid fuel and formation of a pool of liquid fuel, a more efficient burn, and easier lighting. However, difficulty in lighting the wick may be encountered. For this reason, a starter bump, 6, of fuel, is provided in close proximity to the surface of the wick. As illustrated, this bump is most easily molded directly into the shape of the fuel element, and provides a ready source of liquid fuel to the wick when a match or

other appropriate source of flame is employed to start the wick burning, which source of flame will melt the starting bump.

The melting plate of Figures 1 and 2 is shaped so as to have a raised outer shoulder, 22, thereby containing the resultant pool of melted fuel. It is to be understood that the melting plate may be in the form of a tray, bowl, concave plate, or other configuration which is capable of holding a pool of hot liquid fuel, and is so shaped as to funnel or channel the liquified, i.e. melted, fuel to the wick. The bowl shape of Figures 1 and 2 is a preferred embodiment. The melting plate may constitute a container in itself, as shown, or may also be surrounded by a separate container, as illustrated in Figures 5 through 9, hereinafter. In the embodiment shown in Figures 1 and 2, the melting plate rests upon a non-conductive base, 17, or legs of non-conductive or insulating material, so as to permit placement upon a table, counter, or other surface. The non-conductive base, as illustrated, comprises contact points, 25, so as to minimize the amount of contact between the base and the melting plate, and to create an insulating air gap, 27, between the melting plate and the surface upon which the assembly rests.

The melting plate may be of any heat conductive material, such as brass, aluminum, steel, copper, stainless steel, silver, tin, bronze, zinc, iron, clad materials, heat conductive polymers, ceramics, glass, or any other suitable heat conductive material or combination of such materials. As shown in Figure 2, the fuel is preferably located in direct contact with the surface of the melting plate, 2, which plate may, if desired, be constructed so as to have a non-conductive lower surface, so that the melting plate may rest upon a table surface or such. Such a configuration may result from a clad material, a conductive material coated with a non-conductive material, a non-conductive material having an insert of a heat conductive material, or other suitable arrangements to permit the melting plate to be cool enough on the bottom surface to permit ease of handling, and/or placement upon surfaces not suitable for contact with heated bodies, and as shown in Figure 5, for example.

The wick, 3, preferably constitutes a conventional wicking material, such as such as cotton, cellulose, nylon, or paper, or a porous ceramic, fiber glass, or pumice wick, or the like, which by capillary action will carry liquid fuel to the flame. Suitable permanent or non-consumable wicks may comprise such materials as porous ceramics; porous metals; fiber glass; metal fiber; compressed sand, glass, metal, or ceramic microspheres; foamed or porous glass, either natural or man-made, such as pumice or perlite; gypsum; and chalk. In addition, non-combustible materials such as metal may be used to create capillary grooves, spaces, or tubes in or between closely spaced sheets. However, for purposes of the present invention, the use of conventional consumable wicks is preferred. The wick, 3, may be located in the center of the melting plate, 2, or may be off-center as desired, provided that the melting plate is configured so as to channel or funnel the melted fuel to said wick. The presence of two or more wicks is also within the scope of the present invention, as is the use of wicks which are provided as part of the melting plate assembly, a wick holding heat fin assembly, or as part of a removable separate heat clip or wick holder. When provided as an element of the melting plate, the wick may be attached to, adhered to, or incorporated in any manner which does not inhibit the capillary action of the wick in feeding liquid fuel to the flame.

The fuel may be a solid fuel which is liquified, i.e. melted, before or during consumption, such as any conventional candle wax, such as petrolatum or a micro-wax, including paraffin, beeswax, montan wax, carnauba wax, microcrystalline wax, stearic acid, fatty alcohols, fatty acids, fatty esters, or the like, or gels incorporating such fuels, having melting temperatures above ambient, but below the flame temperature of a wick burning such fuel. Such solid fuel may be colored for decorative effect, if so desired, and may be shaped to fit any given configuration of melting plate. For example, the bottom of a solid fuel element should be curved complementarily to the shape of the melting plate upon which it is to rest. Further, the solid fuel may take the form of wax pucks, donuts, chips, slivers, balls, pellets, shavings, particulates, cubes, discs, three dimensional shapes, and wafers, or the like, in sizes suitable for ease of addition to the melting plate or

fuel pool. The solid fuel element may further contain actives such as fragrances, herbals, disinfectants, air purifiers, insecticides, or insect repellents, to be evaporated from the fuel pool as a result of the temperature of said pool being elevated above the melting temperature of the solid fuel by the melting plate and heat  
5 conductive elements.

An important aspect of the present invention is the additional use of a heat conductive element in conjunction with the melting plate, or as part of the melting plate. In addition to taking the form of a heat conductive lobe in or on the surface of the melting plate, the heat conductive element may take the form of a portion  
10 of a heat conductive wick holder which aids in positioning of the wick, or may be present merely as a heat fin, to aid in heat distribution by the conduction of heat from the flame to the fuel. Such heat conductive elements may take a variety of shapes, as exemplified by Figures 3a through 3g, which illustrate various suitable heat conductive elements, but clearly do not illustrate all possible configurations.  
15 The heat conductive element may support or hold the wick, as in Figures 3b, 3e, 3f, and 3g, or may merely pass through the flame or be concentric thereabout without contacting the wick, as in Figures 3a, 3c, and 3d, so as to collect the greatest amount of heat possible from the flame. Shown in conjunction with a wick, the heat conductive element is designed to be in close proximity to, or in  
20 direct contact with, a flame upon said wick, so as to provide a heat collection and distribution member. In these drawings, the wick, 3, is in heat exchange proximity to various forms of heat conductive elements or fins, which act as heat distribution means. The distance of the heat conductive element from the flame should be controlled so as to achieve a suitable degree of heat exchange, i.e. the  
25 heat fin should be less distant from the flame than that distance at which radiant heat from the flame would exceed the amount of heat collected and conducted by the heat fin to the fuel or the melting plate. Due to the variable heat conductivity of materials suitable for use in heat conductive elements, it is not feasible to designate a specific distance between the flame and the heat conductive element or fin, but it is clear that the greatest conductive heat transfer to the fuel  
30 and the melting plate occurs when a highly conductive heat fin passes directly



through the hottest portion of the flame, and that the amount of heat transferred to a heat conductive element or heat fin decreases as the distance from the flame increases. The heat collected from the flame by the heat conductive element, or heat fin, is transferred directly, by conduction, to fuel which is in contact  
5 with the heat fin, or to the melting plate, and thence to fuel which is in contact with the melting plate. The rate of heat flow by conduction greatly exceeds the rate of heat transfer resulting from the radiant heat generated at the flame, resulting in a more efficient use thereof. Thus, the fuel element is melted more rapidly, and the melted fuel is heated to a greater extent, than it would be absent  
10 the heat conductive elements.

In Figure 3a, a helical wire, 8, surrounds the wick, (again, not drawn to scale) 3, and the flame (not shown) which rises therefrom during consumption of the fuel. The helical wire which, with its heat conductive mounting means, 10,  
15 comprises a form of heat fin assembly, 9, may be directly encompassed by a solid fuel element, or mounted upon or into a melting plate, in such a manner that conductive heat transfer loss is minimized. The helical wire is in close proximity to the wick and thus the flame, but may also pass directly through the flame for greater heat transfer. The heat which is collected by the helical wire passes directly, by conduction, to the melting plate 2, via mounting means 10, and to any  
20 fuel which is in contact with the helical wire fin.

Figure 3b illustrates a heat conductive wick holder, 7, in which a wick, 3, is held by mounting means, 10, to project a short distance above the wings or fins, 11, of the holder. The fins, 11, preferably are fashioned of a highly heat conductive metal. The conductive wick holder, 7, comprising the wick mounting means,  
25 10, and the fins, 11, may provide positioning means, 12, designed to engage corresponding recesses or positioning elements within the solid fuel element, or in the melting plate (not shown).

Similarly, Figure 3c illustrates a heat fin assembly, 9, comprising a circular heat fin, 14, surrounding the wick, 3, and having perforations, 15, or holes therein  
30 to permit flow of air and liquid fuel from the outermost side thereof to the innermost side thereof to fuel the burning of the fuel at the wick, 3. The metallic fin,

14, may also comprise a metal mesh, rather than a perforated metal foil as illustrated. This type of heat fin may also be directly attached to the melting plate, or may incorporate a wick clip, 10, by means of which the heat fin may be incorporated within a solid fuel element. It may be seen that the heat fin is so positioned, surrounding the wick and in close proximity thereto, so as to receive heat by radiation from the flame on the wick, which heat is then transmitted by conduction to the melting plate.

Figure 3d illustrates a heat fin assembly, 9, having a clip mounting means, 10, suitable for inclusion in a solid fuel element, and having fins, 11, parallel to the wick itself. Such a heat fin assembly is particularly suitable for use in a melting plate as shown in Figure 4.

Figure 3e shows a heat fin assembly comprising a wick holder, 7, and a single fin, 11, configured so as to pass through the flame above the wick, 3, in such a manner as to collect and distribute the maximum amount of heat available. In this configuration of wick holder, the wick is positioned by mounting means 28, e.g. a clamp or encircling ring, while the holder may be positioned in place in a solid fuel element during preparation thereof by means of positioning means 12, or other suitable means.

It is to be emphasized that the heat generated at the flame is conducted by means of heat conductive elements to both the melting plate and to the solid fuel, causing it to liquify or melt, thus providing a pool of liquid fuel, 5, as shown in Figures 4 and 5, which is available to the wick to support further combustion. As illustrated in Figures 1 and 2, the solid fuel is located above and in direct contact with the melting plate, which also serves to contain the solid fuel and the liquid fuel derived therefrom by the melting thereof. The direct contact of the melting plate and the solid fuel improves heat flow to the fuel, ensuring a more rapid and complete melting thereof. As the fuel is consumed by the flame, additional melted fuel will be channeled or funneled to the wick as a result of the shape of the melting plate being designed to accomplish such flow. Additional fuel elements may be introduced as desired or necessary, to replenish those which are consumed, or if desired, to change or modify the fuel being consumed.

One preferred embodiment of the use of the melting plate technology of this invention may be referred to as a melting plate candle, 18, as illustrated, for example, in Figures 4 and 5. Figure 4 shows a one piece construction, favorable for low cost production, which uses a wick holder, 7, having fins 11, and in which the entire remaining assembly may be considered to constitute a melting plate. As shown, the melting plate, 2, is shaped so as to provide a bowl shaped container, 20, having a central depression, 16, for placement of a fuel element incorporating a heat conductive wick holder, 7. In a melting plate candle produced in this form, the wick holder, 7, functioned both to position the wick, 3, and to transmit heat, via fins 11, from the flame, 1, to the fuel as well as to the melting plate, 2, which constituted the container for the pool of melted wax, 5. For this illustration, the solid fuel element is not shown, but the fuel is shown as having been completely melted, at which point the wick is supported in position by the wick holder, 7. The wax pool was formed by the melting of a solid fuel element, such as paraffin, which was placed in the bowl shaped container, 20, and melted by heat conducted from the flame by the fins to the melting plate, 2. The height of the raised shoulder, 22, of the bowl shaped container was chosen so as to provide a pool of adequate depth to contain a sufficient supply of fuel to burn for a desired period of time. By use of a highly heat conductive metal, such as aluminum or copper, for the melting plate, and proper dimensioning of the unit, the entire mass of the solid fuel element added to the bowl was rapidly melted from the bottom, resulting in a pool of fuel, 5, which filled the bowl sufficiently to ensure a lengthy burn time. As the level of the pool dropped, additional wax, in the form of chips, shavings, granules, cubes, or small balls, was added, and rapidly melted. It is to be noted that while the melting plate candle, 18, illustrated by Figure 4 was essentially circular, the shape is not critical, and may be varied, such as in the form of a square, triangle, oval, rectangle, clover, diamond, etc, provided that it is shaped so as to channel the liquid fuel to the wick. It is also possible to locate the wick, 3, in an off-center location, for esthetic effect or for increased efficiency, dependent upon the shape and dimensions chosen for the melting plate, or to employ a plurality of wicks located at various positions within

the bowl. Raised portions, or lobes, may be present to define separate zones within such various shapes, and/or to facilitate heat conduction. For example, a clover shaped melting plate may be produced, having separate wicks and fuel elements containing a different coloring material in each of the leaves of the clover, with raised portions separating the zones, and each such zone configured to channel the liquified fuel to the wick located therein. Such a melting plate offers the opportunity for the consumer to choose among varying fuels, or to burn one, two, three, or more wicks at any given time.

A second example of a melting plate candle, 18, is shown in Figure 5, wherein a two piece construction is illustrated, also having a pool of fuel, 5, constituted of melted wax. In this design, the wick, 3, is proximate a heat lobe, 19, a raised portion of the melting plate, 2. The heat conductive element, or lobe, conducts heat to the rest of the melting plate, which is so shaped as to engage and/or partially rest upon the sides or slope of a non-conductive container, 26. The container may be made of any suitable material, such as glass, ceramic, plastic, wood, etc., and may be of any desired shape, the selection of such being determined, for example, by esthetics. The melting plate is configured in such a manner as to leave an insulating air gap, 27, between the melting plate and the container to limit heat transfer to the container, for safety, as well as to permit the greatest possible heat transfer from the melting plate to the pool of fuel, 5. As with the one piece construction melting plate of Figure 4, the melting plate may preferably be constructed of a stamped heat conductive metal. In this illustration, the wick, 3, is shown as being positioned within the central depression, 16, of the melting plate, proximate the lobes or heat conductive elements, 19, of the melting plate. The melting plate and lobes may also be designed to conduct the heat from the flame in a non-concentric pattern, allowing shapes other than round. Thus, by use of heat conducting lobes, constituting raised areas of the melting plate, melting plates may be oval, triangular, rectangular, or any other desired shape.

Exemplary of the various shapes which may be utilized is an oval heat plate candle, such as shown in Figures 6 and 7. Shown is a melting plate can-

dle, 18, comprising an oval non-conductive container, 26, in which is located a melting plate, 2, not shown, but present under the pool of liquified fuel, 5, said melting plate having raised lobes 19, in close proximity to a flame 1, centrally located. Arrows, 24, indicate the direction of conductive heat flow away from the flame via the melting plate, to enhance the melting of fuel, and heating of the pool of fuel located upon the surface of the melting plate. The melting plate is so configured as to cause the flow of liquified or melted fuel to the base of the wick, whereby it is consumed in the flame.

As previously stated, the heat conductive elements, such as lobes, may be so configured as to aid in location of the solid fuel element, particularly for location of solid fuel refill elements, as shown in Figures 8, and 9. As shown in Figure 8, a non-conductive container, 26, was provided, which held a melting plate, 2, in the manner shown in Figure 5, in juxtaposition to heat conductive lobes, 19. The lobes, as illustrated, were so configured as to act as a positioning device for a solid fuel refill element, 21, having wick 3. The lobes were situated upon a heating plate, 2, having a recess therein (not shown) into which the refill element was inserted so as to provide close proximity of the flame, 1, on the wick, 3, to lobes 19. As illustrated, the lobes provide two recesses for positioning of refill elements, although only one refill element is shown. The heat from the flame was transmitted to the solid fuel both by radiation, and by conduction through lobes 19 and the melting plate, 2, to rapidly melt the fuel, creating a pool of liquid fuel, 5. In this embodiment, the refill element comprised a cylindrical wax body similar to a votive candle, with a conventional wick. Other shapes of refill elements, such as balls, were added to the heating plate after consumption of the original fuel element. The convex shape of the melting plate assisted in both locating the refill elements and in assuring flow of melted fuel to the base of the wick, and the wick was retained in position by the wick clip of the candle element in the recess. Additional fuel refill elements were also found to be readily melted by the melting plate candle shown. Refill elements in the shape of discs, cubes, balls, pucks, and various other three dimensional shapes were also used. This configuration was also found to permit easy change of any active materials

desirably dispersed, by virtue of the second position for placement of a refill element, whereby refill elements having differing active ingredients could easily be alternated, just as refill elements of differing color could be alternated.

Another form of solid fuel candle which may employ the melting plate and  
5 heat fin technology of this invention is the floating melting plate candle. Conventional floating candles are known to tunnel very rapidly and to leave a high percentage of unburned wax, due to the cooling effect of the water upon which they float. A floating melting plate was tested, with an insulating air gap, in conjunction with a heat fin assembly holding the wick, which insulated the wax from the  
10 body of water upon which the melting plate floated, while heating of the wax was improved, so as to maintain a liquid wax pool for more uniform and more complete consumption of the fuel. As shown in Figure 9, a container, 26, retained a body of water, 30, upon which floated a melting plate candle, 18. The melting plate candle comprised a bowl shaped container, 20, having a melting plate, 2, seated therein, so as to form an insulating air gap, 27. The melting plate had a  
15 central depression, 16, into which was placed a wax fuel element, 21, comprising a heat conductive wick holder, 7, with a heat fin 11, and a retained wick, 3. The wax fuel element, 21, fitted around the wick holder, in close proximity thereto, whereby heat was transferred efficiently from the flame, 1, at wick 3, by the heat  
20 fin assembly to the melting plate, which thus improved melting of the wax, thereby forming a pool of liquid fuel. The outside container, 26, represents any suitable container for retention of a pool of water, or other liquid of choice, sufficient for floating a melting plate candle, such as a bath tub, sink, bowl, or pool. The melting plate container, 20, may be made of any suitable material, such as  
25 glass, ceramic, plastic, wood, etc, and may be of any desired shape, the selection of such being determined, for example, by esthetics, provided that the container be able to float safely on water while a heated fuel is disposed therein. The solid fuel segment may be of any shape, color, configuration, or composition consistent with the present invention, designed to properly fit the melting plate  
30 configuration. Examples of suitable refill segments would include circular, star, clover, or flower bud or petal shapes, or any three dimensional form selected, in

red, white, yellow, blue, green, or other colors, either plain or fragranced by various perfumes, or containing various other active ingredients which will volatilize at the temperature of the liquid fuel pool formed in the bowl of the melting plate. In a conventional form of floating candle, a wax candle of low density is provided  
5 in a desired shape, configuration, and color, much in the fashion of the candle refill segments described above. In such candles, the wick is normally affixed with a conventional wick clip, and passes through the central portion of the wax body. Such candles, when floated in a body of water, suffer from short burning life, cratering, and drowning. Applicants have found that the use of a heat con-  
10 ductive wick holder, heat fins, and melting plate as illustrated in Figure 9, provided a floating candle which burned until all of the fuel therein was consumed. The shape of such floating melting plate candles may be of almost any configuration desired, with the wick holder being located centrally, or otherwise, and either single or plural. Shaping of the fuel element to any configuration is possible,  
15 as is the use of coloration for decorative purposes, along with a wide choice of actives, such as fragrances, to be included.

Similarly, when using solid fuel, such as wax, in conjunction with a heat fin or wick holder, solid fuel refill units may be shaped to fit the shape of the con-  
20 tainer, configured to fit the shape of the melting plate, in a "lock and key" relationship. For example, the melting plate may be a decoratively shaped container, and wax may be provided in the form of refills for the container shape selected, such as a round, square, star, clover, triangle, or other three dimensional shape, so shaped as to fit around and engage a complementarily shaped lobe or heat  
fin, for example.

25 The use of a melting plate with additional heat conductive elements offers a number of distinct advantages. First, it permits a larger pool of liquid fuel, due to improved heat conduction into the fuel, which results in more rapid formation of the pool. This in turn allows better regulation of the size and temperature of the liquified wax pool to allow more efficient use of fuels present. In fact, melting  
30 plates permit ease of refill, with little or no cleaning. The use of lobes in the heat plate in conjunction with heat fins in the fuel element also reduces or eliminates

retention of solidified excess fuel when the candle is allowed to burn itself out, and permits more complete and uniform burning of fuel elements which are other than round, i.e. square, oval, triangular, or in the shape of a flower or decorative object, etc. Further, the melting plate technology results in devices which may be self extinguishing, and improvements in or elimination of typical burning problems encountered with candles, such as tunneling, drowning, collapsing, cratering, and wick drift. Candles utilizing the melting plate technology of the present invention are also more forgiving of formulation or process variances.

## EXAMPLES

A number of tea lights were prepared to test the efficiency of the invention relative to heat distribution and melting of the wax fuel. In the following Examples, all candles comprised the same wax, and were of the same dimension, with identical consumable wicks. Examples comprised tea lights with conventional wick clips in a conventional aluminum container, tea lights with conventional wick clips but no container, and tea lights with a finned wick clip and heat plate as set forth in the present invention. Temperatures of the wax pool were measured at distances of 10 and 20 mm from the wick, using infrared temperature measuring methods.



Table 1

Time vs. Temperature (° F) 10 mm from wick			
Minutes	Regular clip Regular container	Regular clip No container	Finned Clip Heat Plate
10	148	147	115
15	147	142	121
20	144	137	128
25	142	139	136
30	141	137	144
40	144	139	128
50	146	138	146
60	154	141	177
70	168	138	203
80	170	143	208
90	172	142	200
120	171	143	172
150	158		

In this experiment, the regular clip / regular container tea light burned out after 152 minutes, the regular clip / no container tea light burned out after 123 minutes, and the finned clip tea light burned out after 125 minutes. It may be seen that the tea light employing the finned clip achieved a much higher temperature in the wax pool than either of the other tea lights, exceeding a temperature of about 180° F at a distance of about 10 mm from the wick.

Table 2

Time vs. Temperature (° F) 20 mm from wick			
Minutes	Regular clip Regular container	Regular clip No container	Finned Clip Heat Plate
10	78	80	79
15	80	138	83
20	80	118	87
25	82	107	89
30	85	113	91
40	88	119	93
50	89	128	130
60	93	127	165
70	97	136	172
80	99	139	174
90	102	137	167
120	108	119	135
150	117		

In this experiment, the regular clip / regular container tea light burned out after 152 minutes, the regular clip / no container tea light burned out after 123 minutes, and the finned clip tea light burned out after 125 minutes. It may be seen that the tea light employing the finned clip achieved a much higher temperature in the wax pool than either of the other tea lights, exceeding a temperature of about 160° F at a point about 20 mm from said wick.

While the present invention has been described with respect to what are at present considered to be the preferred embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments. To the contrary, the invention is intended to cover various modifications and equivalent arrangements within the spirit and scope of the appended claims. The scope of the

following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent formulations and functions.

#### INDUSTRIAL APPLICABILITY

5

The melting plate and heat conductive element candles of the present invention can be used in connection with a large variety of solid fuels. The conductive materials of which the melting plate and heat fins may be constructed are commonly available, and the various configurations are readily produced. There is considerable interest for candles having extended burn times, and for refillable candles or solid fuel lamps.

10

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2